

Combined beacon and siren unit. Available in several colours. Powered by 24 V DC gives loud audio signal and bright visual alarm, to ensure that call will be answered. For noisy areas such as engine rooms

**FEATURES**

- 2 stage alarm
- Rugged construction
- 32 selectable tones meeting international regulations
- Enclosure in ABS flame retardant plastic
- Monitoring facility
- High sound output
- Stainless steel fixings
- Sound selection via DIP switch
- All sides cable entry
- EX certified available (Optional)



Mounting: Via internal fixing holes

The PFEER sound signals recommended by UKOOA are:

General Alarm	Sound Signal 15	Interrupted tone 1000 Hz
PAPA	Sound Signal 31	Reverse Sweep 1200-500 Hz
Toxic Gas	Sound Signal 11	Continuous Tone 1000 Hz

**SPECIFICATIONS**

Sound output	100dBA @ 1 mtr Max
Operating voltage	Ⓔ / DC / 230V AC
Relative humidity	95% @ 40°C
IP rating	IP-55
Operating temp.	-25°C to +40°C
Dimmension (W x H x D)	90 x 180 x 81
Weight	0,49 kg
Approvals / Compliance	BASEEFA EN60079-0:2006 EN60079-11:2007 II 1G Ex.ia IIC

