UCR-010R CABINET SPEAKER

Cabinet speaker with innovative design. The symmetrical shape adapts to all premises in the best way. It can also be used as a ceiling speaker. High quality speaker element provides excellent psound quality.








Side view with additional volume control

## **FEATURES**

- Easy assembly, grille can be lifted off with a screwdriver by losing two screws
- Multiple surface mounting. Can be mounted horizontal, vertical or to the ceiling
- Impact and scratch resistant chassis
- Fitted with volume control available on request (Optional)
- Version with built in relay available (Optional - suffix R)
- Available in a moisture proof impregnated Optional)
- Available in all RAL colors (Optional)

SPECIFICATIONS	
Load rating (music capacity)	10 (15) W
Impedance	100 V / 8 Ω
Transformer tappings	10 / 5 / 2.5 W
Frequency range	150 - 20000 Hz
Sound pressure at 1W / 1m	94.5 dB
SPL Pmax/1m	105 dB at 1.3 kHz
Angle of refl. beam (-6dB) 1 / 4 / 8 kHz	180°/60°/50°
Speaker diameter - Φ	130 mm
Dimensions (H x W x D)	270 x 204 (221) x 66 mm
Weight	Approx. 1.1 kg
Colour	Alpinewhite
Approvals/ Compliance	CE BS 5839 (Optional)

MOUNTING SCREWS HOLES



221

REAR VIEW

uller International Communication

204