

Small, quadratic ceiling and wall speaker, which is also suitable for the installation in 100 mm conduits. Design and a harmonized choice of colour perfectly matches any premises. A wide band speaker ensures excellent sound for voice transmission as well as for background music purposes.



Cable channel instalation

FEATURES

- Can operate both in 100V line and as low impedance (8 ohms, 6W)
- Assembling through two mounting springs ensure secure hold
- Adjustable to any usual wall / ceiling thicknesses
- Possible to instal in cable channel
- Available in a moisture proof version (Optional)
- Special speaker colours are available (Optional)
- Possible delivery with 20 cm wire and connection clamp (Optional)
- Available in 10 W version (Optional)



Secure hold and easy assembly with two springs

SPECIFICATIONS

Load rating (music capacity)	6 W
Impedance	100 V / 8 Ω
Transformer tappings	6 / 4 / 2 W
Frequency range	110 - 20000 Hz
Sound pressure at 1W / 1m	87 dB
SPL Pmax/1m	95 dB at 0.3 kHz
Angle of refl. beam (-6dB) 1 / 4 / 8 kHz	180° / 100° / 180°
Speaker diameter - Φ	64 mm
Dimensions (W x H x inst. depth)	105 x 105 x 72 mm
Weight	Approx. 0.5 kg
Approvals/ Compliance	CE

