

The UTH horn speaker have to be combined with required driver system. Available UDS horn driver systems can be delivered in both 100V line and low impedance version. With the selection of the appropriate system, it is possible to produce a suprlative sound pressure. Recommended for roof loudhailer.



UTH-360



UTH-510

FEATURES

- Easy assembly and wide setting range of UTH horn speaker provided by fixing bracket
- Special sound coverage requirements can be fulfilled, thanks to many possible combination
- Excellent dynamic sound quality
- Totally weather-proof construction (IP-66)
- International commonly used thread fitting (1 3/8") enables combinations with any other required driver system
- Stable aluminum metallic-grey
- Stove enameled funnels are attached with a rubber protection ring

HORN SPEAKER SPECIFICATION

	UTH-360	UTH-510
Low frequency cutoff	appr. 200 Hz	appr. 170 Hz
Connection thread	1 3/8", international	
Horn material	aluminium	
Colour	grey-metallic	
Dimmensions (φ, L)	360, 310 mm	510, 390 mm
Weight approx.	1,5 kg	2,2 kg



UDS-100T

HORN DRIVER SPECIFICATION

	UDS-60T	UDS-100T	UDS-60	UDS-100
Load rating	60 W	100 W	60 W	100 W
Tapping / Impedance	60 / 40 / 20 W	100 / 60 / 40 W	16 Ω	16 Ω
Frequency response	200 - 8000 Hz	160 - 10000 Hz	190 - 8000 Hz	180 - 8000 Hz
Sund pressure at 1W/1m	110 dB	110 dB	106 dB	108 dB
Dimmensions (φ, H)	110, 160 mm	110, 160 mm	114, 112 mm	120, 123 mm
Weight approx.	2,4 kg	3,3 kg	2,0 kg	2,5 kg



UDS-100